

STAINLESS STEEL 316 CABLE CLEATS - TREFOIL

Heavy Duty Stainless Steel Cable Cleat For Cables In Trefoil Formation

316L STAINLESS STEEL FRAME AND FIXINGS

SOFT LSF POLYMERIC LINER PROTECTS CABLE SHEATH

CAPTIVE CLOSURE FIXINGS FOR FAST INSTALL

SHORT CIRCUIT AND MECHANICALLY TESTED TO IEC 61914

ABS, DNV, UL AND LUL APPROVED



Stainless Steel Trefoil Cable Cleat

Part No.	Cable Range mm (inch)			Dimensions mm (inch)	
	Min. Dia.	Mid.Dia.	Max.Dia.	H	W
CCT1823	18 (0.71)	20 (0.79)	23 (0.91)	79 (3.11)	82 (3.23)
CCT2328	23 (0.91)	25 (0.98)	28 (1.10)	84 (3.31)	93 (3.66)
CCT2732	27 (1.06)	29 (1.14)	32 (1.26)	91 (3.58)	99 (3.90)
CCT3035	30 (1.18)	33 (1.30)	35 (1.38)	96 (3.78)	103 (4.06)
CCT3338	33 (1.30)	35 (1.38)	38 (1.50)	101 (3.98)	107 (4.21)
CCT3642	36 (1.42)	38 (1.50)	42 (1.65)	107 (4.21)	113 (4.45)
CCT4046	40 (1.57)	44 (1.73)	46 (1.81)	114 (4.49)	119 (4.69)
CCT4450	44 (1.73)	47 (1.85)	50 (1.97)	121 (4.76)	126 (4.96)
CCT4855	48 (1.89)	51 (2.01)	55 (2.17)	129 (5.08)	137 (5.39)
CCT5158	51 (2.01)	53 (2.09)	58 (2.28)	134 (5.28)	143 (5.63)
CCT5562	55 (2.17)	57 (2.24)	62 (2.44)	141 (5.55)	152 (5.98)
CCT5966	59 (2.32)	64 (2.52)	66 (2.60)	148 (5.83)	161 (6.34)
CCT6370	63 (2.48)	65 (2.56)	70 (2.76)	155 (6.10)	169 (6.65)
CCT6774	67 (2.64)	69 (2.72)	74 (2.91)	161 (6.34)	178 (7.01)
CCT7178	71 (2.80)	73 (2.87)	78 (3.07)	168 (6.61)	186 (7.32)
CCT7482	74 (2.91)	76 (2.99)	82 (3.23)	175 (6.89)	195 (7.68)
CCT7785	77 (3.03)	80 (3.15)	85 (3.35)	180 (7.09)	202 (7.95)
CCT8288	82 (3.23)	84 (3.31)	88 (3.46)	185 (7.28)	208 (8.19)
CCT8896	88 (3.46)	92 (3.62)	96 (3.78)	199 (7.83)	225 (8.86)
CCT96103	96 (3.78)	100 (3.94)	103 (4.06)	210 (8.27)	240 (9.45)
CCT103111	103 (4.06)	107 (4.21)	111 (4.37)	224 (8.82)	258 (10.16)
CCT111119	111 (4.37)	115 (4.53)	119 (4.69)	237 (9.33)	275 (10.83)
CCT119128	119 (4.69)	124 (4.88)	128 (5.04)	253 (9.96)	295 (11.61)

Construction Data of the Cable Cleats

- Cleat Material: Composite
- Metallic Frame: 50mm*2.1mm, marine grade, Non-magnetic 316L
- Closure Hardware: 316L SS M8, M10 or M12 bolt and Nylon Lock Nut
- Integral Pad: Low Smoke, Low Fume, Halogen Free
- Tools Required: Wrench
- Mounting Bolt: Provided with the Cable Cleat

Performance on the Cable Cleats IEC61914:2021

- Resistance to Electromechanical Force :
Test Cable Outer Dia :35mm
9.5.2 180kA Perk 300mm Spacing
9.5.3 125kA Perk 600mm Spacing
- Lateral Load Test: Avg. 25kg
- Axial Load Test: Pass
- Max - Min Temperature: -40°C~60°C
- Resistance to Impact
- Needle Flame Test: 30 Seconds
- Resistant to UV Light Test: 1000 hours

