



# POLYAMIDE (PA66)

## UV PROOF CABLE TIE



Type 21  
POSITIONING DEVICE  
43KU E75050-18T1  
GT-540HD-S



### MEGALOK

- . Available in a wide range of materials
- . Internal serrations allowing for a possible hold onto cable and pipe bundles
- . The design of the head guarantees a high tensile strength while allowing a very low insertion force
- . Flame retardant, heat stabilized weather resistant are available
- . Material: Polyamide 6.6, UL94V-2 UV-Stabilized cable tie resist UV-radiation
- . Color: All colors are available



| Part.No   | Length |       | Width |      | Max.Bundle Dia. |       | Min. Loop tensile strength |     | operating temperature |                 |
|-----------|--------|-------|-------|------|-----------------|-------|----------------------------|-----|-----------------------|-----------------|
|           | mm     | inch  | mm    | inch | mm              | inch  | kgf                        | lbs | Max.                  | Min.            |
| GT-100M   | 100    | 3.94  | 2.5   | 0.1  | 22              | 0.87  | 8.1                        | 18  | 85° C (185° F)        | -40° C (-40° F) |
| GT-150I   | 150    | 5.91  | 3.6   | 0.14 | 35              | 1.38  | 18.2                       | 40  | 85° C (185° F)        | -40° C (-40° F) |
| GT-200I   | 200    | 7.87  | 3.6   | 0.14 | 53              | 2.09  | 18.2                       | 40  | 85° C (185° F)        | -40° C (-40° F) |
| GT-200ST  | 200    | 7.87  | 4.8   | 0.19 | 50              | 1.97  | 22.6                       | 50  | 85° C (185° F)        | -40° C (-40° F) |
| GT-250ST  | 250    | 9.84  | 4.8   | 0.19 | 60              | 2.36  | 22.6                       | 50  | 85° C (185° F)        | -40° C (-40° F) |
| GT-300ST  | 300    | 11.81 | 4.8   | 0.19 | 76              | 2.99  | 22.6                       | 50  | 85° C (185° F)        | -40° C (-40° F) |
| GT-370ST  | 370    | 14.57 | 4.8   | 0.19 | 102             | 4.02  | 22.6                       | 50  | 85° C (185° F)        | -40° C (-40° F) |
| GT-370HD  | 370    | 14.57 | 7.6   | 0.3  | 102             | 4.02  | 54.4                       | 120 | 85° C (185° F)        | -40° C (-40° F) |
| GT-430ST  | 430    | 16.93 | 4.8   | 0.19 | 110             | 4.33  | 22.6                       | 50  | 85° C (185° F)        | -40° C (-40° F) |
| GT-450ST  | 450    | 17.72 | 4.8   | 0.19 | 116             | 4.57  | 22.6                       | 50  | 85° C (185° F)        | -40° C (-40° F) |
| GT-450HDS | 450    | 17.72 | 7.6   | 0.3  | 132             | 5.20  | 54.4                       | 120 | 85° C (185° F)        | -40° C (-40° F) |
| GT-530HD  | 526    | 20.71 | 9     | 0.35 | 140             | 5.51  | 79.4                       | 175 | 85° C (185° F)        | -40° C (-40° F) |
| GT-630HD  | 610    | 24.02 | 9     | 0.35 | 187             | 7     | 79.4                       | 175 | 85° C (185° F)        | -40° C (-40° F) |
| GT-710HD  | 710    | 27.95 | 9     | 0.35 | 190             | 7.48  | 79.4                       | 175 | 85° C (185° F)        | -40° C (-40° F) |
| GT-780HD  | 778    | 30.55 | 9     | 0.35 | 228             | 8.98  | 79.4                       | 175 | 85° C (185° F)        | -40° C (-40° F) |
| GT-830HD  | 815    | 32.09 | 9     | 0.35 | 239             | 9.41  | 79.4                       | 175 | 85° C (185° F)        | -40° C (-40° F) |
| GT-920HD  | 916    | 36.06 | 9     | 0.35 | 263             | 10.35 | 79.4                       | 175 | 85° C (185° F)        | -40° C (-40° F) |
| GT-1220HD | 1220   | 48.03 | 9     | 0.35 | 365             | 14.37 | 79.4                       | 175 | 85° C (185° F)        | -40° C (-40° F) |
| GT-1530HD | 1530   | 60.24 | 9     | 0.35 | 460             | 18.11 | 79.4                       | 175 | 85° C (185° F)        | -40° C (-40° F) |

