



STAINLESS STEEL 316 BALL LOCK TYPE

CABLE TIES POLYESTER COATED



#316
Stainless Steel
for extra corrosive
environments



- MEGALOK stainless steel ties are designed to secure hoses, cables, poles, pipes, and more when harsh environmental conditions may adversely affect the bundling application
- Used where corrosion, vibration, weathering, radiation, and temperature extremes are a concern, MEGALOK stainless steel ties can be used in virtually any indoor, outdoor, and underground application
- Self locking, ball bearing mechanism for quick and easy installation, either by hand or by tensioning tool
- AISI 316 stainless steel for the most corrosive environments
- Polyester coating provides additional edge protection and prevents corrosion between dissimilar metals
- UV resistant, low smoke, halogen-free material
- Material: Stainless steel type: #304, #316
Coating: Polyester coated tie
- Length: All lengths are available

Part No.	Length (L) mm (inch)	Width (W) mm (inch)	Thickness (T) mm (inch)	Max.Bundle ø mm (inch)	Min. Loop Tensile Strength		
					N	kgf	lbf
MG-TB6C130ST	129 (5.08)	4.45 (0.18)	0.25 (0.01)	33 (1.30)	445	45.4	100
MG-TB6C200ST	200 (7.87)	4.45 (0.18)	0.25 (0.01)	50 (1.97)	445	45.4	100
MG-TB6C300ST	300 (11.81)	4.45 (0.18)	0.25 (0.01)	76 (2.99)	445	45.4	100
MG-TB6C370ST	370 (14.57)	4.45 (0.18)	0.25 (0.01)	102 (4.02)	445	45.4	100
MG-TB6C520ST	520 (20.47)	4.45 (0.18)	0.25 (0.01)	156 (6.14)	445	45.4	100
MG-TB6C680ST	680 (26.77)	4.45 (0.18)	0.25 (0.01)	207 (8.15)	445	45.4	100
MG-TB6C840ST	840 (33.07)	4.45 (0.18)	0.25 (0.01)	257 (10.10)	445	45.4	100
MG-TB6C1050ST	1050 (41.34)	4.45 (0.18)	0.25 (0.01)	319 (12.56)	445	45.4	100
MG-TB6C200HD	197 (7.76)	7.96 (0.31)	0.25 (0.01)	50 (1.97)	1112	113.4	250
MG-TB6C300HD	300 (11.81)	7.96 (0.31)	0.25 (0.01)	76 (2.99)	1112	113.4	250
MG-TB6C370HD	368 (14.49)	7.96 (0.31)	0.25 (0.01)	102 (4.02)	1112	113.4	250
MG-TB6C450HD	450 (17.72)	7.96 (0.31)	0.25 (0.01)	135 (5.31)	1112	113.4	250
MG-TB6C500HD	500 (19.69)	7.96 (0.31)	0.25 (0.01)	150 (5.93)	1112	113.4	250
MG-TB6C680HD	680 (26.77)	7.96 (0.31)	0.25 (0.01)	207 (8.15)	1112	113.4	250
MG-TB6C720HD	720 (28.35)	7.96 (0.31)	0.25 (0.01)	216 (8.50)	1112	113.4	250
MG-TB6C840HD	840 (33.07)	7.96 (0.31)	0.25 (0.01)	257(10.10)	1112	113.4	250
MG-TB6C1020HD	1020 (40.16)	7.96 (0.31)	0.25 (0.01)	312 (12.30)	1112	113.4	250
MG-TB6C1050HD	1050 (41.34)	7.96 (0.31)	0.25 (0.01)	319 (12.56)	1112	113.4	250

